

FORTINO® The little wind resistant sunshade

Glatz
Shade in Swiss Quality



Point of use



Fixations



In the lounge or at the bar: the little FORTINO® is there wherever you need shade. Thanks to its size, it can change location quicker than you can say Jack Robinson. The opposite servo principle means that it is easy to use: simply pull the tension lever down and clip it onto the slider. The frame is made from naturally anodised aluminium, with a two-part grooved pole. With its stable construction, the FORTINO® is wind resistant and can be fixed onto multiple bases or a floor fitting.





Beach Hamburg

Material and technology

Frame:	8 rods made of natural anodized aluminium, 100 % inox, screws and rivets of high-grade steel, two-part profiled pole 38.4 × 2 mm, contrarotating opening system allowing for easy opening.	Protective cover:	optional
Framematerial:	anodized natural	Total height closed:	280–305 cm
Frameform:	round or square	Height open:	245–265 cm
Shade cover:	self-tautening thanks to the flexible rod ends material class 5 (100 % polyacrylic approx. 300 g/m ²) material class 4 (100 % polyester approx. 250 g/m ²) material class 2 (100 % polyester approx. 220 g/m ²)	Wind:	max. wind speed open perm. 80 km/h
Flounce:	not available	UV protection:	depending on colour ≥ 98 % (based on test results of "Swiss Quality Testing Services")
		Light fastness:	material class 4 and 5 = Level 7–8
		Water pressure:	material class 4 = water column 100 mm material class 5 ≥ water column 300 mm (depending on colour)

Assortment

	Nominal size cm	Lateral distance cm	Area covered m ²	Height closed cm	Clear headroom cm	Total height cm	Height open cm	Foundation cm	Minimum weight for base kg	max. wind speed open perm. km/h (wind force)	Order no. Frame anodized natural
	⁹ Ø 250	230	4.4	155	205	290	260	60 × 60	55	80 (9)	310 00 250 171
	¹³ Ø 270	250	5.2	145	205	295	260	60 × 60	55	65 (8)	310 00 270 171
	⁹ Ø 300	275	6.4	140	205	305	265	70 × 70	70	60 (7)	310 00 300 171
	⁹ 200 × 200	-	4.0	130	205	280	245	60 × 60	55	70 (8)	310 00 201 171
	⁹ 240 × 240	-	5.8	115	205	295	250	70 × 70	70	60 (7)	310 00 241 171

¹ while stocks last



⁹ 8 parts

The listed measures represent extrapolated average values that may be slightly different on the product ($\pm 2\% \pm 5$ cm).


Height dimensions are based on ground socket BT. These vary slightly depending on the type of base. Except for steel base minus 5 cm.

The max. wind speed limits as per our separate list apply only in the presence of a fix ground anchorage.

In the presence of several sunshades, the minimum distance between one sunshade and another and between sunshades and walls shall be 20 cm.



8 parts




8 parts

Loose cover max. 10 cm, concrete thickness
min. 30 cm (pay attention to frost depth),
water outflow

Accessories

	Order no.
Fixing option Z (support tube Z absolutely necessary)	
1. Concrete base Z, 55 kg, $\varnothing 60 \times 11$ cm	350 01 109 528
1. Concrete base Z, 70 kg, $\varnothing 75 \times 9$ cm	350 01 109 527
2. ³ Granite base Z, 55 kg, $55 \times 55 \times 9$ cm, natural stone, with castors and retractable handle	350 01 109 440
3. Steel base Z, 40 kg, $58.5 \times 58.5 \times 2$ cm, galvanised steel	350 01 100 210
Add-on weight 30 kg, $57.5 \times 57.5 \times 1.7$ cm, galvanised steel	350 01 100 310
4. Wall bracket Z, 180 mm, galvanised steel	350 01 205 000
5. Support tube Z, $\varnothing 35 / 38 - 39$ mm, galvanised steel	350 01 201 010
5. Support tube Z, $\varnothing 35 / 38 - 39$ mm, high-grade steel 1.4301 / 304	350 01 201 100
³Base with castors (Weight set absolutely necessary)	
6. Base frame with castors 60 kg, $\varnothing 61 \times 12$ cm, anthracite, with support tube $\varnothing 35 / 38 - 39$ mm, polished aluminium (Base frame ca. 17 kg)	350 01 102 400
Weight Set, 4 pieces 35001105400, concrete, for base with castors 60 kg (Weight Set ca. 43 kg)	350 01 103 400
Protective cover for base with castors 60 kg	350 01 602 400
Fixing option BT (Connection tube BT absolutely necessary)	
7. Ground socket BT, galvanised steel	350 01 206 100
8. Connection tube BT, $\varnothing 35 / 38 - 39$ mm, galvanised steel	350 01 206 210
Protective cover, coated polyester fabric	
9. Protective cover with zip and rod	350 01 609 971

³only suitable for smooth, joint free surface coverings





Majorca



El Paradiso, St. Moritz



The Oitavos, Cascais PRT