

TEAKWOOD The Rolls Royce of classic sunshades

Glatz
Shade in Swiss Quality



Point of use



Fixations



Material and technology

Frame: 8 rods made of teak, continuous pole \varnothing 48 mm, with a double pulley to facilitate easy opening.

Frame material: teak

Frame shape: round or square

Shade cover: with leather reinforcements
material class 5 (100% polyacrylic approx. 300 g/m²)
material class 4 (100% polyester approx. 250 g/m²)

Flounce: not available

Protective cover: included in the standard equipment

Note: The wood is supplied in a natural and therefore untreated state. The wood may secrete colourings and its own natural oils which may leave residues behind on a light coloured cover. This cannot be avoided and is therefore not admissible as a complaint.

Assortment

	Nominal size cm	Lateral distance cm	Pole Ø cm	Area covered m ²	Height closed cm	Clear headroom cm	Total height cm	Foundation cm	Minimum weight for base kg	max. wind speed open perm. km/h (wind force)	Order no. Frame teak
○	A	AS	M	B	E	F	G	C			
	³ Ø 300	275	4.8	6.4	135	220	285	60 × 60	40	30 (5)	166 00 300 731
	³ Ø 350	325	4.8	8.7	105	215	285	60 × 60	55	30 (5)	166 00 350 731
□	³ 330 × 330	-	4.8	10.9	45	220	285	60 × 60	70	30 (5)	166 00 331 731


³8 parts

The listed measures represent extrapolated average values that may be slightly different on the product ($\pm 2\% \pm 5$ cm).


The height dimensions are based on the ground socket PX. In the base variations these might differ slightly. Apart from the steel base minus 7.5 cm.

The max. wind speed limits as per our separate list apply only in the presence of a fix ground anchorage.


In the presence of several sunshades, the minimum distance between one sunshade and another and between sunshades and walls shall be 20 cm.



Loose cover max. 10 cm, concrete thickness min. 30 cm (pay attention to frost depth), water outflow



8 parts



8 parts

Accessories

	Order no.
Fixing option Z (support tube Z absolutely necessary)	
1. Concrete base Z, 40 kg, Ø 60 × 8.5 cm	350 01 109 529
1. Concrete base Z, 55 kg, Ø 60 × 11 cm	350 01 109 528
1. Concrete base Z, 70 kg, Ø 75 × 9 cm	350 01 109 527
2. Granite base Z 40 kg, Ø 53 × 7 cm, natural stone	350 01 109 460
3. ³ Granite base Z, 55 kg, 55 × 55 × 9 cm, natural stone, with castors and retractable handle	350 01 109 440
4. Steel base Z, 40 kg, 58.5 × 58.5 × 2 cm, galvanised steel	350 01 100 210
Add-on weight 30 kg, 57.5 × 57.5 × 1.7 cm, galvanised steel	350 01 100 310
5. Wall bracket Z, 180 mm, galvanised steel	350 01 205 000
6. Support tube Z, Ø 48 / 55 mm, galvanised steel	350 01 201 210
6. Support tube Z, Ø 48 / 55 mm, high-grade steel 1.4301 / 304	350 01 201 300
Fixing option PX (Connection tube PX absolutely necessary)	
7. Ground socket PX, galvanised steel	350 01 207 001
7. Ground socket PX, high-grade steel 1.4301 / 304	350 01 207 011
8. Connection tube PX, Ø 48 / 55 mm, galvanised steel	350 01 206 001
8. Connection tube PX, Ø 48 / 55 mm, high-grade steel 1.4301 / 304	350 01 206 011
Protective cover, coated polyester fabric	
9. Protective cover with zip and rod	350 01 609 969
Miscellaneous items	
10. Rechargeable battery light Osyrion 8 for pole Ø 48 – 68 mm, battery charger with european plug (type C) included (1 accumulator included)	350 01 557 960
11. Rechargeable battery light Osyrion 6 for pole Ø 30 – 50 mm, battery charger with european plug (type C) included (1 accumulator included)	350 01 557 950
12. Rechargeable battery light Osyrion 4 for pole Ø 30 – 50 mm, battery charger with european plug (type C) included (1 accumulator included)	350 01 557 910
Spare accu, 3.7 V, 4800 mAh (for Osyrion 8)	350 01 557 970

³only suitable for smooth, joint free surface coverings

